

GreenGuard®

Professional Flashing

For use with building wrap, sheathing, windows, doors and other openings to create a complete water-resistant seal.



- Blocks water infiltration around windows and doors
- Butyl adhesive
- Economical self-adhering membrane

GreenGuard[®] Professional Flashing

Description

Kingspan GreenGuard[®] Professional Flashing is a self-adhering flashing membrane comprising a polyolefin film with a butyl adhesive.

Kingspan GreenGuard[®] Professional Flashing is an economical self-adhering flashing membrane. It is designed to seal the interface around wall penetrations such as windows, doors, pipe penetrations, and other areas that may require a weatherproof seal.

Installation

To obtain the best adhesion, Kingspan GreenGuard[®] Professional Flashing should be installed over surfaces that are free of dirt and moisture.

Placement by hand, then it is necessary to apply strong pressure with a j-roller to ensure adhesion.

Compliance

AAMA 711;

Handling & Storage

Store boxes containing Kingspan GreenGuard[®] Professional Flashing in a clean, dry area without prolonged, direct exposure to sunlight. Kingspan GreenGuard[®] Professional Flashing has a shelf life of approximately one year.

WARNING: This product is combustible. A protective barrier or thermal barrier is required as specified in the appropriate building code. Protect it from exposure to open flame or other ignition sources during shipping, storage and installation.

WARNING: The release paper of Kingspan GreenGuard[®] Professional Flashing is slippery and should not be walked on at any time. Discard release paper in a designated container.



Please scan the QR code for the most recent product information.

Product Data		
Property	Test Method	Value
General		
Material Thickness (in) (mils)		0.016 16
Nominal Width (in)		4/6/9/12/18
Backing Material		HDPE
Adhesive		Butyl
Application Temp., Min. (°F)		20-180
Recommended Service Temp., Max. (°F)		300
Outdoor /UV Exposure, Max. (days)		80
Nail Sealability	AAMA 711-07 Modified D-1970	Pass

For more information on specific building product recommendations and installation guidelines, contact your Kingspan Insulation LLC representative.

Kingspan Insulation LLC believes the information and recommendations herein to be accurate and reliable. However, since use conditions are not within its control, Kingspan Insulation LLC does not guarantee results from use of such products or other information herein and disclaims all liability from any resulting damage or loss. No warranty, express or implied, is given as to the merchantability, fitness for particular purpose, or otherwise with respect to the products referred to.

Kingspan Insulation LLC
2100 Riveredge Parkway | Suite 175
Atlanta | Georgia 30328

T: +1 (800) 241 4402 F: +1 (678) 589 7325

E: info@kingspaninsulation.us

www.kingspaninsulation.us

© Kingspan, the G Device and the Lion Device are Registered Trademarks of the Kingspan Group plc in the US, Canada and other countries. All rights reserved.

© GreenGuard is a Registered Trademark of the Kingspan Group plc in the US. All rights reserved.

kingspan-green-guard-professional-flashing-product-data-sheet-en-us-v2.1

Version 2.1 - 12/2022

